



GLOBAL HEALTH

GHP-9080 80L
WATERPROOF
CONSTANT
TEMPERATURE
INCUBATOR



GHP-9080 80L WATERPROOF CONSTANT TEMPERATURE INCUBATOR

Box of high quality cold-rolled steel, surface electrostatic spray, coating hard solid, with a strong anti-rust capability.

PRODUCT DESCRIPTION

- Chamber size: 800x600x600mm
 - Appearance size: 900x700x700mm
 - Temperature range: 0-50°C
 - Temperature resolution: 0.1°C
 - Temperature fluctuation: ±0.1°C
 - Temperature uniformity: ±0.2°C
 - Operating ambient temperature: +5-35°C
- Temperature controller: Using the most advanced technology home and abroad Microprocessor PID controller, the inside temperature exceeds the set value, the water level is too high or too low of water jacket, which automatically sends light alarm, low water level automatic water, it includes a specified front and automatic stop, automatic water control automatic stop, ensure it's not easy to burn out the electrical heated tube when the products, with no water. Make no loss of product and secure. Independent limit temperature alarm system, automatically interlocks if the temperature exceeded the limit. Ensure the experiments can safely without accident.
- Water jacket application: 100% cooler
 - Low material Chamber: High quality stainless steel, waterproof heating, temperature uniformity, and will not keep constant temperature after outage.
 - Heating structure: High quality stainless steel, surface electrostatic spray, coating hard solid, with a strong anti-rust capability.
 - Heating structure: 100% cooler, the low temperature control system is accurate, the high temperature cycle, there is no contact and heating automatically stop, no overheating.
 - Sensor: Class A PT100 platinum resistance
 - Air flow: Horizontal circulation and left to right transfer temperature uniformity, dual insulated heater, refrigeration, temperature sensor.
 - Heating structure: 100% cooler
 - Safety: Built-in 900 watt temperature, grounding protection
 - Built-in data: temperature
 - Temperature: 0-50.000 Celsius
 - Power supply: 220V 50Hz
 - www.gmsh.com